



附注:

1. 未标注R角0.05mm;
2. 引脚端面须电镀, 引脚电镀层要求: Ni层2.5um MIN, 锡层6um MIN;
3. 最大毛边允许0.1mm;
4. 产品符合RoHS环保要求.

⑳	增加20号尺寸进行管控, (即贴平面尺寸)		万祥青 (2015.08.22)	A/2
⑨	7.7±0.10	7.7+0/-0.10	万祥青 (2015.08.22)	A/2
⑤	8.7±0.15	8.7+0/-0.15	万祥青 (2015.08.22)	A/2
④	3.60±0.05	3.50±0.05	万祥青 (2015.08.05)	A/1
标记	原来尺寸	更改后尺寸	签名(日期)	REV

Drawn by	梁进华	Tolerances		Material	PM-9630	TITEL: EOP-6
Checked by		0<L≤5	±0.10	PIN Material	C5191铜线	
Approved by	万祥青	5<L≤20	±0.15	UL REC	94-V0	Part name: KD009-04-P2B
 康达盛五金塑胶电子有限公司 TEL:0752-6310283 FAX:0752-6310233	Coler			Coler	Black	 REV A/2 DATE 2015.08.05
	Unit			Unit	mm	
	Scale			Scale	5:1	