



②	5.04±0.1	4.90+0.08/-0.05	梁进华(2015.8.18)
⑧	7±0.1	7.15±0.05	梁进华(2015.5.28)
②	4.90+0.15/-0.1	5.04±0.1	梁进华(2015.5.28)
⑮	2.95	2.67	万祥青(2014.3.17)
⑭	4.3±0.1	4.52±0.2	万祥青(2014.3.17)
⑪	9.3±0.2	9.27±0.2	万祥青(2014.3.17)
⑨	3.55±0.05	3.5±0.05	万祥青(2014.3.17)
①	8.25±0.2	7.92±0.2	万祥青(2014.3.17)
标记	原来尺寸	更改后尺寸	签名(日期)

- 附注:
1. 未注圆角为R0.05-0.2mm;
  2. 最大毛边允许0.05mm;
  3. 端子平面度: 0.1mm Max;
  4. 产品符合RoHS环保要求;
  5. 端子硬度为1H(HV 190-210) 偏上限, 硬度必须在HV200度以上。

Drawn by	梁进华	Tolerances		Material	PM-9630	TITEL: EP-7(有定位柱)
Checked by		0<L≤5	±0.10	PIN Material	C5191	
Approved by	万祥青	5<L≤20	±0.15	UL REC	94-V0	Part name: KD010-03-P1B
				color	Black	
				Unit	mm	REV A/3
				Scale	5:1	DATE 2014.03.26



康达盛五金塑胶电子有限公司

TEL:0752-6310283/6310239 FAX:0752-6310233