



附注:

1. 未注圆角为R0.05-0.2mm;
2. 最大毛边允许0.05mm;
3. 端子平面度: 0.1mm Max;
4. 产品符合RoHS环保要求.

|    |          |          |                    |
|----|----------|----------|--------------------|
|    | 删除⑬尺寸    |          | 梁进华 (2014. 12. 09) |
| ⑳  | 0.5      | 0.7      | 梁进华 (2014. 11. 08) |
| ㉑  | 3.90±0.1 | 4.00±0.1 | 万祥青 (2013. 5. 13)  |
| ㉒  | 4.90±0.1 | 5.00±0.1 | 万祥青 (2013. 5. 13)  |
| 标记 | 原来尺寸     | 更改后尺寸    | 签名(日期)             |

|             |     |            |       |              |         |                         |
|-------------|-----|------------|-------|--------------|---------|-------------------------|
| Drawn by    | 梁进华 | Tolerances |       | Material     | PM-9630 | TITEL: EPC-10           |
| Checked by  |     | 0<L≤5      | ±0.10 | PIN Material | C5191   |                         |
| Approved by | 万祥青 | 5<L≤20     | ±0.15 | UL REC       | 94-V0   | Part name: KD036-01-P1B |
|             |     |            |       | color        | Black   |                         |
|             |     |            |       | Unit         | mm      | REV A/3                 |
|             |     |            |       | Scale        | 4:1     | DATE 2014. 12. 09       |



康达盛五金塑胶电子有限公司

TEL:0752-6310283/6310239 FAX:0752-6310233