


附注:

1. 未注圆角为R0.05-0.2mm;
2. 最大毛边允许0.05mm;
3. 端子平面度: 0.1mm Max;
4. 产品符合RoHS环保要求.
5. 端子硬度为全硬190° -210°

3	万祥青 (2014. 11. 19)	⑩ 尺寸0.70改为0.70±0.05
2	万祥青 (2014. 11. 19)	更改端子硬度 (半硬170° -190° 改为全硬190° -210°)
1	梁进华 (2014. 11. 06)	增加端子硬度要求
REV	签名(日期)	更改内容

Drawn by	梁进华	Tolerances		Material	PM-9630	TITEL: EFD-20 (6+6PIN) 高脚				
Checked by		0<L≤5	±0.10	PIN Material	C5191					
Approved by	万祥青	5<L≤20	±0.15	UL REC	94-V0	Part name: KD083-03-P1B				
				color	Black					
				Unit	mm	 <table border="1"> <tr> <td>REV</td> <td>A/0</td> </tr> <tr> <td>DATE</td> <td>2014. 11. 06</td> </tr> </table>	REV	A/0	DATE	2014. 11. 06
REV	A/0									
DATE	2014. 11. 06									
				Scale	3:1					



康达盛五金塑胶电子有限公司

TEL:0752-6310283/6310239 FAX:0752-6310233