



- 附注:
1. 未标注R角0.15mm;
 2. 引脚端面须电镀, 引脚电镀层要求: Ni>=0.625um, 100%锡>=5.0um;
 3. 最大毛边允许0.1mm;
 4. 产品符合RoHS环保要求;
 5. 端子平面度: 0.1mm MAX.

A/3	7号尺寸从之前的15.60±0.2改为15.60+0.0/-0.2	万祥青 (2015. 6. 08)
A/2	14号尺寸从之前的4.6改为4.6±0.05	万祥青 (2015. 5. 19)
A/1	产品名称变更为KD085-01-P2B	万祥青 (2015. 5. 14)
A/1	材料变更为PM-9630	万祥青 (2015. 5. 14)
REV	更改内容	签名(日期)

Drawn by	梁进华	Tolerances	Material	PM-9630	TITEL:	EP-13(4+8PIN)
Checked by		0<L≤5 ±0.10	PIN Material	C5191磷青铜		
Approved by	万祥青	5<L≤20 ±0.15	UL REC	94-V0	Part name:	
 康达盛五金塑胶电子有限公司 TEL:0752-6310283 FAX:0752-6310233			color	Black	Ⓢ  REV A/3 DATE 2014. 09. 29	
			Unit	mm		
			Scale	4:1		