



附注:

1. 未注圆角为R0.05-0.2mm;
2. 端子拉力: 1.4KG Min;
3. 最大毛边允许0.05mm;
4. 端子平面度: 0.1mm Max;
5. 产品符合RoHS环保要求。
6. 端子硬度为全硬190° -210°

A/2	万祥青 (2014. 11. 20)	⑦号尺寸更改公差 (21.35±0.15改为21.35±0.20)
A/1	梁进华 (2014. 11. 06)	增加端子硬度要求
REV	签名(日期)	更改内容

Drawn by	梁进华	Tolerances		Material	PM-9630	TITEL: EFD-15 (5+5PIN)				
Checked by		0 < L ≤ 5	±0.10	PIN Material	C5191					
Approved by	万祥青	5 < L ≤ 20	±0.15	UL REC	94-V0	Part name: KD029-11-P1B				
				color	Black					
				Unit	mm	  <table border="1"> <tr> <td>REV</td> <td>A/2</td> </tr> <tr> <td>DATE</td> <td>2014. 11. 06</td> </tr> </table>	REV	A/2	DATE	2014. 11. 06
REV	A/2									
DATE	2014. 11. 06									
				Scale	3:1					



康达盛五金塑胶电子有限公司

TEL:0752-6310283/6310239 FAX:0752-6310233