


附注:

1. 未注圆角为R0.05-0.2mm;
2. 端子拉力: 1.4KG Min;
3. 最大毛边允许0.05mm;
4. 端子平面度: 0.1mm Max;
5. 产品符合RoHS环保要求;

1	万祥青 (2015.12.01)	17号尺寸由2.5变更为2.4
1	万祥青 (2015.12.01)	13号尺寸由3.1变更为3.2
1	万祥青 (2015.12.01)	6号尺寸由2.2变更为2.3
REV	签名(日期)	更改内容

Drawn by	梁进华	Tolerances	Material	PM-9630	TITEL: EP-13(4+5PIN) BOBBIN				
Checked by		0<L≤5 ±0.10	PIN Material	CP WIRE					
Approved by	万祥青	5<L≤20 ±0.15	UL REC	94-V0	Part name: KD098-04-P3B				
			color	Black					
			Unit	mm	 <table border="1"> <tr> <td>REV</td> <td>A/1</td> </tr> <tr> <td>DATE</td> <td>2012.04.13</td> </tr> </table>	REV	A/1	DATE	2012.04.13
REV	A/1								
DATE	2012.04.13								
			Scale	3:1					



康达盛五金塑胶电子有限公司

TEL:0752-6310283/6310239 FAX:0752-6310233