



附注:

1. 未注圆角为R0.05-0.2mm;
2. 最大毛边允许0.05mm;
3. 端子平面度: 0.1mm Max;
4. 产品符合RoHS环保要求;
5. 引脚电镀要求:
 1. 镍层厚度: 1-3 μm;
 2. 锡层厚度: 5-10 μm.

| | | | |
|----------|------|------------------|--------|
| 图纸胶芯增加栅格 | | 梁进华 (2015.02.06) | |
| 标记 | 原来尺寸 | 更改后尺寸 | 签名(日期) |

| | | | | | |
|-------------------------------------------------------------------------------------------------------------------------------------------------|-----|------------|-------|--------------|---------|
| Drawn by | 梁进华 | Tolerances | | Material | WH-9100 |
| Checked by | | 0 < L ≤ 5 | ±0.10 | PIN Material | C5191 |
| Approved by | 万祥青 | 5 < L ≤ 20 | ±0.15 | UL REC | 94-V0 |
|  康达盛五金塑胶电子有限公司 TEL: 0752-6310283/6310239 FAX: 0752-6310233 | | | | color | Black |
| | | | | Unit | mm |
| | | | | Scale | 5:1 |

| | |
|-------------------------|------------|
| TITEL: 48PIN CASE | |
| Part name: KD124-01-H1A | |
| REV | A/1 |
| DATE | 2015.02.06 |