



附注:

1. 未注圆角为R0.05-0.2mm;
2. 最大毛边允许0.05mm;
3. 端子平面度: 0.1mm Max;
4. 产品符合RoHS环保要求.
5. PIN脚电镀要求:
 1. 镍层厚度: 1-3 μm;
 2. 锡层厚度: 3-10 μm.
6. 带"*"号尺寸不作为测量尺寸.

A/2	梁进华 (2015. 11. 25)	产品尺寸编号变更以及增加20、23、24、25、26尺寸标注
A/1	梁进华 (2015. 11. 21)	19号尺寸由6.95±0.1变更为6.91±0.1
A/1	梁进华 (2015. 11. 21)	16号尺寸由5.95±0.05变更为5.9±0.05
A/1	梁进华 (2015. 11. 21)	6号尺寸由8+0/-0.15变更为7.88±0.1
A/1	梁进华 (2015. 11. 21)	5号尺寸由5.05±0.1变更为5.01±0.1
A/1	梁进华 (2015. 11. 21)	3号尺寸由4.8+0.08/-0.05变更为4.8±0.05
REV	签名(日期)	更改内容

Drawn by	梁进华	Tolerances		Material	PM9630	TITEL: PMDPMEP05-02
Checked by		0<L≤5	±0.10	PIN Material	C5191	
Approved by	万祥青	5<L≤20	±0.15	UL REC	94-V0	Part name: KD163-01-P1B
 康达盛五金塑胶电子有限公司 TEL:0752-6310283/6310239 FAX:0752-6310233	color				Black	 REV A/2 DATE 2014.09.11
	Unit				mm	
	Scale					