



- 附注:
1. 未标注R角0.2mm;
  2. 电镀要求:  
镍层50-100uIN,  
锡层300-500uIN;
  3. 最大毛边允许0.1mm;
  4. 产品符合RoHS环保要求;
  5. 端子平面度: 0.076mm MIN;
  6. 端子拉力: 1.4KG MIN.

A/1	万祥青 (2015. 12. 05)	18号尺寸公差变更为0.085±0.002
A/1	万祥青 (2015. 12. 05)	15号尺寸公差变更为0.06±0.002
REV	签名(日期)	更改内容

Drawn by	梁进华	<small>UNLESS OTHERWISE SPECIFIED, ALL DIMENSIONS ARE IN INCHES. TOLERANCES ARE:</small> <small>DECIMALS</small> .XX ±.01 <small>ANGLES</small> ± 1° <small>DO NOT SCALE DRAWING</small>	Material	PM-9630	TITEL: EE-5.0(3+3PIN)	
Checked by			PIN Material	C5191		
Approved by	万祥青		UL REC	94-V0	Part name:	KD192-01-P1C
			color	Black		
		Unit	mm			
		Scale	10:1			
					REV A/1	
					DATE 2015.6.04	



康达盛五金塑胶电子有限公司

TEL:0752-6310283 FAX:0752-6310233